

Project
Type
Date
Cat #

Application Features

Commercial-grade, LED modular linear luminaire with direct and indirect illumination. This luminaire features a narrow design and is ideal for architectural applications that require clean and uniform lines.



Specifications

Optical System

Standard top clear diffuser and bottom frosted diffuser are both lay-in lenses.

Mounting

Standard aircraft cable for suspended-mount application (nominal 4 foot suspension). Suitable for row-mounting, see ordering key for various configurations.

Construction

Precision-formed steel housing assembly.

Finish

White, polyester powder painted housing.

Electrical

Long life LEDs coupled with high efficiency drivers provide quality illumination. Rated to deliver L80 performance > 50,000 hours. Supplied with dimmable drivers (0-10v). Standard 4 foot nominal white, single-circuit. All electrical components are CSA approved or UL listed.

Approvals

Approved to CSA/UL standards. Rated for damp locations.

Warranty

5 year limited warranty. For complete warranty terms visit: http://viscor.com/assets/Viscor_LED_Warranty.pdf

Features

- Frosted Lenses
- Continuous row-mounting capability
- 80+ CRI
- Standard low voltage dimming driver (0-10V)

Options & Adders

- Available in direct/indirect and direct configurations
- Emergency Lighting Battery Pack (Remote Mount Only)
- Downlight only option available

Applications

- Office Areas
- Perimeters
- Retail Stores
- Corridors
- Classrooms
- Libraries
- Hospitality

LED

ARCHITECTURAL LIGHTING

Dimensions



