

SUBJECT:

# ALRB

# INSTRUCTION SHEET

**WARNING: ELECTRICAL SHOCK POTENTIAL !!** DO NOT ATTEMPT TO INSTALL, MAINTAIN OR RELAMP WITHOUT DIS-CONNECTING ALL POWER, FAILURE TO DISCONNECT POWER CAN RESULT IN ELECTROCUTION, SHOCK OR SEVERE BURNS. ONLY QUALIFIED PERSONNEL TO CONDUCT ELECTRICAL INSTALLATION.

|                        |     |     |
|------------------------|-----|-----|
| Nominal fixture length | 4ft | 8ft |
| Canopy Spacing         | 43" | 87" |

**Step 1.**  
Disconnect power.

**Step 2.**  
Install canopy sets (cross bar, threaded rod, canopy, cable coupler, AC cable, power cord) and connect power cord. For canopy spacing refer to table provided.

**Step 3.**  
Install cable grippers via 1/4-20 threaded rods (supplied) to the fixture and hang the fixture inserting AC cables through cable grippers. Adjust suspension height as required and level the fixture.

**Step 4.**  
Remove fixture cover and connect power to the fixture utilizing strain relief (provided) and make wiring connections according to local electrical codes.

**Step 9.**  
Reinstall covers.

