

													
Model	Alto	Bevel	Revel	ClearForm	OnCurve Concave & OnCurve Concave - Spine	OnCurve Convex	OnCurve Wave	Quadra	LTDCR	Outline (Type I)	Outline (Type U)	Outline (Type O)	Outline (Type L)
Grade	Premium	Premium	Premium	Premium	Premium	Premium	Premium	Premium	Specification	Specification	Specification	Specification	Specification
Cost	\$\$	\$\$	\$\$	\$\$	\$\$	\$\$	\$\$	\$\$\$	\$\$\$	\$\$\$	\$\$\$	\$\$\$	\$\$\$
Size	Imperial: 1x4, 2x2, 2x4	Imperial: 1x4, 2x2, 2x4 Metric: 20x60	Imperial: 1x4, 2x2, 2x4 Metric: 20x60	Imperial: 1x4, 2x2, 2x4 Metric: 30x30, 20x60, 750x750, 500x1500	Imperial: 1x4, 2x2, 2x4 Metric: 20x60	Imperial: 2x2	Imperial: 2x4, 4x4	Imperial: 2x2, 4x4	Imperial: 1x1, 2x2, 3x3, 4x4	Imperial: 2x2 (Single/Double LED Bar)	Imperial: 2x2 (U-Shape LED Bar)	Imperial: 2x2 (O-Shape LED Bar)	Imperial: 2x2 (L-Shape LED Bar)
Height	Imperial: 3.25"	Imperial: 4" Metric: 4"	Imperial: 4" Metric: 4"	Imperial: 3 1/2" Metric: 3 1/2" & 90 mm	Imperial: 4.5" Metric: 4.5"	Imperial: 4.5"	Imperial: 4.5"	Imperial: 5"	Imperial: 5" & 7.5"	Imperial: 2.5"	Imperial: 2.5"	Imperial: 2.5"	Imperial: 2.5"
Standard Lens	Frosted single-piece 1.25" regressed diffuser	Two removable angled frosted diffusers with a flat center rail	Two removable angled frosted diffusers with a flat rail	Frosted single-piece formed polycarbonate diffuser	Frosted lay-in concave single-piece diffuser	Frosted lay-in convex single-piece diffuser	2x4 - Frosted curved double-piece lay-in diffusers 4x4 - Frosted curved quadruple-piece lay-in diffusers	Fabricated opal white acrylic diffuser	Concave opal acrylic diffuser	Frosted laser formed one-piece diffuser	Frosted laser formed one-piece diffuser	Frosted laser formed one-piece diffuser	Frosted laser formed one-piece diffuser
Standard Dimming	(0-10V) 1%	(0-10V) 1%	(0-10V) 1%	(0-10v, 10%)	(0-10V) 1%	(0-10V) 1%	(0-10V) 1%	(0-10v, 10%)	(0-10v, 10%)	(0-10V) 1%	(0-10V) 1%	(0-10V) 1%	(0-10V) 1%
Lumen Packages	2,000 - 7,000	2,500 - 7,000	2,500 - 7,000	3,700 - 10,000	2,000 - 7,000	2,400 - 5,000	2x4: 3,600 - 7,000 4x4: 5,000 - 14,100	2x2: 2,000 - 4,000 4x4: 8,000 - 16,000	800 - 10,500	500 - 3,000	1,500 - 4,500	2,000 - 6,000	1,000 - 3,000
Systeme Watts	16 - 54 w	19.3 - 52.1 w	20 - 60 w	28 - 76 w	17 - 54 w	19 - 41.5 w	2x4: 28.5 - 57 w 4x4: 37 - 101 w	2x4: 19 - 36 w 4x4: 70 - 142 w	13 - 100 w	5 - 31 w	14.5 - 45.7 w	18.3 - 58.8 w	9.6 - 31.3 w
Approvals & Ratings	<ul style="list-style-type: none"> ETL Listed RoHS Compliant 	<ul style="list-style-type: none"> ETL Listed DLC Listed TAA Compliant 	<ul style="list-style-type: none"> ETL Listed DLC Listed TAA Compliant 	<ul style="list-style-type: none"> CSA/UL Standard DLC Listed 	<ul style="list-style-type: none"> ETL Listed DLC Listed 	<ul style="list-style-type: none"> ETL Listed DLC Listed 	<ul style="list-style-type: none"> ETL Listed 	<ul style="list-style-type: none"> UL Listed 	<ul style="list-style-type: none"> UL Listed 	<ul style="list-style-type: none"> UL Listed 	<ul style="list-style-type: none"> UL Listed 	<ul style="list-style-type: none"> UL Listed 	<ul style="list-style-type: none"> UL Listed
Notable Options & Features	<ul style="list-style-type: none"> Chicago Plenum Housing Tunable White Plenum Side Access for servicing Aperture Profile: <ul style="list-style-type: none"> Square Corners Rounded Corners 	<ul style="list-style-type: none"> Air Supply/Return Slots Chicago Plenum Housing Tegular Tile Housing Tunable White Room Side Service Access Metric / Non-Standard Sizes: <ul style="list-style-type: none"> Optional filler plates Optional full illumination 	<ul style="list-style-type: none"> Air Supply/Return Slots Chicago Plenum Housing Tegular Tile Housing Tunable White Room Side Service Access Metric / Non-Standard Sizes: <ul style="list-style-type: none"> Optional filler plates Optional full illumination 	<ul style="list-style-type: none"> Air Supply/Return Slots Chicago Plenum Housing Tegular Tile Housing Alternate Lens Overlays Bi-Level w/ Red Led Array Shallow Plenum Room Side Service Access Metric / Non-Standard Sizes: <ul style="list-style-type: none"> Optional filler plates Optional full illumination C29 Construction: <ul style="list-style-type: none"> Wet Location NSF 	<ul style="list-style-type: none"> Air Supply/Return Slots Chicago Plenum Housing Tegular Tile Housing Centre Spline with Color Options Room Side Service Access Metric / Non-Standard Sizes: <ul style="list-style-type: none"> Optional filler plates Optional full illumination 	<ul style="list-style-type: none"> Chicago Plenum Housing Room Side Service Access 	<ul style="list-style-type: none"> Room Side Service Access 	<ul style="list-style-type: none"> Chicago Plenum Housing Lens Depth Options: <ul style="list-style-type: none"> Flush 1" Drop 2" Drop 3" Drop 4" Drop Room Side Service Access 	<ul style="list-style-type: none"> Convex Lens Optional Flat Opal diffuser Impact Resistant Frosted Overlay Lens Tamper Resistant Fasteners Room Side Service Access 	<ul style="list-style-type: none"> Tegular Tile Housing Plenum Side Access Tunable White 	<ul style="list-style-type: none"> Tegular Tile Housing Plenum Side Access Tunable White 	<ul style="list-style-type: none"> Tegular Tile Housing Plenum Side Access Tunable White 	<ul style="list-style-type: none"> Tegular Tile Housing Plenum Side Access Tunable White

Universal to all Recessed Lighting products:

Driver Options	DALI/1%
Approvals & Ratings	<ul style="list-style-type: none"> Suitable for Damp Locations IC-Rated IESNA LM-79
Options & Features	<ul style="list-style-type: none"> Custom lumens EM Battery Pack Flexible Whip
CCT	3,000K - 5,000K
CRI Available	80+ / 90+
L70, L80, L90 Performance	>60,000hrs
Voltage	UNV / 347V
Control Types	Wireless Controls
Mounting Kits	Flange Kits and Surface Kits available for 1x4, 2x2, 2x4

