

Project
Type
Date
Cat #

Application Features

Specification-grade pendant-mounted direct/indirect converted industrial space luminaire. For use with indoor applications where low-glare, high-quality and ease of installation are required.



Specifications

Optical System

Shields are perforated for direct and indirect illumination and contain a opal white acrylic overlay diffuser for visual comfort. Parabolic reflector is contoured to provide soft, low-glare general illumination while providing a high-level of visual comfort.

Mounting

This product can be surface, chain or stem-mounted.

Construction

Die and brake-formed, heavy-gauge steel housing assembly. Precision-formed steel reflector. Die-formed, perforated, cold rolled steel shielding.

Finish

White, polyester powder painted visible surfaces.

Electrical

Rotary lampholders ensure positive lamp retention. Sufficient knockouts are provided for connections and through wiring.

Approvals

Approved to CSA and UL standards.

Features

- Shield hinges from either side for easy re-lamping and re-ballasting
- Single, basket-shaped perforated metal shield
- Parabolic reflector design
- Continuous row-mounting capability
- Surface, stem, or chain mountable
- Available in lengths of 24, 36 or 48 inches
- Available in T5 and T8 configurations


Options & Adders

- Dimmable and Emergency ballast
- Slotted full reflector painted white
- Aircraft cable
- Mounting suspension set
- Speedy hangers
- Stem and canopy sets

Applications

- Corridors
- Retail Stores and Supermarkets
- Studio Lofts

Dimensions



248 Shown

Back View

MODEL	NOMINAL LENGTH A (in.)
224	24
236	36
248	48

