

Project
Type
Date
Cat #

Application Features

Premium-grade enclosed vandal-resistant shallow surface-mounted wrap-around T8 luminaire. For use with indoor and outdoor applications where some dust and moisture resistance is required. This luminaire's shallow design and vandal-resistant injection moulded polycarbonate prismatic diffuser makes it ideal for parkades.



Specifications

Optical System

Injection moulded, thick walled, clear prismatic diffuser is manufactured from high impact, UV treated polycarbonate.

Mounting

Mounting holes are provided. Mounts over electrical junction box.

Construction

Die and brake-formed, code gauge steel housing assembly. Diffuser is held in place and is secured with stainless steel screws.

Finish

High-reflectivity coated reflecting surfaces for improved efficiency.

Electrical

Rotary lampholders ensure positive lamp retention. Sufficient knockouts are provided for connections.

Approvals

Approved to CSA and UL standards.

Features

- Ideal for low ceiling mounting conditions
- Vandal-resistant
- HID alternative or replacement
- Available with 1, 2, or 3 lamp cross section
- Injection moulded polycarbonate prismatic diffuser
- Stainless steel hardware


Options & Adders

- Emergency ballast
- Radio interference filter (120V - 277V)
- Mounting gasketing for back plate
- 20 gauge heavy-duty construction
- Tamper-proof fasteners

Applications

- Canopies
- Corridors and stairwells
- Garage and Workshops
- Locker Rooms
- Parking Garages
- Public Housing
- Security Lighting

Dimensions



MODEL	NOMINAL LENGTH	OVERALL LENGTH A (in.)
124	24"	26 3/16"
224		
324		
148	48"	50 3/16"
248		
348		

