

# ClearForm-Wet Location

LED - Specification-Grade Recessed Luminaire

Project:	Catalogue #:	Type:
Notes:		

## Product Description

Specification-grade enclosed and gasketed luminaire featuring a shallow elliptical center lens. For use with indoor applications where high-efficiency, high performance and ease of installation are required. This IC-rated luminaire's shallow design and dust and moisture resistance, make it ideal for use with indoor and outdoor (canopy) applications that require a wet location recessed lay-in T-Bar/Drywall luminaire with door frame.

## Applications

Outdoor, under covered canopy, Wet and Dusty environments

## Features

- Ideal for shallow or obstructed plenum applications
- Standard low voltage dimming (0-10v)
- 80+ CRI
- Available in 1x4, 2x2, 2x4
- Internal extruded acrylic lens

## Featured Options

- NSF
- Fasteners Tamper Proof
- Microwave Occupancy Sensor

## Optical System

One piece perimeter door frame with clear sealed lens. Internal frosted single-piece Polycarbonate diffuser offer high levels of efficiency and visual comfort. Indirect reflectors are precision formed and contoured to provide soft, low-glare, indirect illumination, while maintaining high-efficiency and a wide, uniform light distribution.

## Mounting

Holes provided for chain-mounting support to building structure. Lay-in type luminaire for exposed grid type acoustical ceiling structure and swing style mounting brackets for drywall ceiling installation.

## Construction

Die-formed and riveted, heavy-gauge steel housing assembly. Precision-formed steel reflector. Wiring access plate and knockouts are provided on back of housing.

## Finish

White, polyester powder painted housing.

## Electrical

Long life LEDs coupled with high efficiency drivers provide quality illumination. Rated to deliver L80 performance > 50,000 hours.

## Warranty

5 year limited warranty. For complete warranty, click here: [5YR Warranty](#)




## Approvals

- Approved to CSA/UL standards. UL listed for insulated ceilings.
- Tested in accordance to IESNA LM-79.
- UL listed for wet locations.



## Dimensions



Size	A	B	C
1x4	47 3/4"	11 3/4"	3 15/16"
2x2	23 3/4"	23 3/4"	3 15/16"
2x4	47 3/4"	23 3/4"	3 15/16"

Consult installation guide for exact dimensions.

Project:	Catalogue #:	Type:
Notes:		

## Order Key

**EXAMPLE: LRTG-C29-2x4-LED840K074LUNV-P94**



<b>Type</b>	<b>CRI</b>	<b>Voltage</b>	<b>Options</b>
<b>Housing Construction Type</b>	8 - (80+)	UNV - 120-277V 347 - 347V	<b>Driver Options</b>
<b>Size (Width x Length)</b>	<b>CCT</b>	<b>Internal Lens</b>	B15 Bi-Level Step Dimming (50/100) (Not available for 347V) B39 Emergency Lighting Battery Pack - LED
1x4 2x2 2x4	30K - 3000K 35K - 3500K 40K - 4000K 50K - 5000K	P94 - Single Piece Polycarbonate	<b>Housing Construction Options</b>
	<b>Nominal Lumens</b>		C03 Fasteners Tamper Proof C32 Chicago Plenum C45 Housing for tegular tiles
	1x4 2x2 2x4		<b>Packaging Options</b>
	040L - 4000 037L - 3700 050L - 5000		K0 Bulk Pack/Pallet Packed and/or Wrapped
	040L - 4000 050L - 5000 074L - 7400 092L - 9200		<b>Interior Diffuser Options</b>
			Frosted Ribbed Linear Acrylic Lens is Standard - P41 C24 Shield Rectangular Perforated Matte White C26 Shield Perforated Hole Pattern Matte White C0 Decorative Lens Rails
			<b>External Diffuser Options</b>
			Clear Acrylic Lens is Standard - P56 P45 Clear Polycarbonate
			<b>Wiring Options</b>
			V09 Flexible Whip (standard 6Ft. x 3-18 ga.) V68 Microwave Occupancy Sensor
			<b>Approval and Rating Options</b>
			X5 NSF - National Sanitation Foundation (Comes with NSF compliant gloss white finish)
			<b>Controls Options</b>
			To view the controls guide <a href="#">Click Here</a> .

\* See Ordering Key.  
Other options may be available, consult factory.  
Specifications and data subject to change without notice.

## Performance Data

LED Performance Data				
Size	Nominal Lumens	Delivered Lumens	Watts	Lumens per Watt
1x4	4000	4092	28.3	144
2x2	3700	3750	27.5	136.2
	5000	5038	38.6	130.3
2x4	4000	4023	27.8	144.5
	5000	5050	35.5	142.1
	7400	7435	54.5	136.4
	9200	9212	69.6	132.3

Values based on 840K with standard lens at 25C

## Performance Scaling Factor

	50K	40K	35K	30K
80CRI	1.000	1.000	0.960	0.946
90CRI	0.875	0.875	0.836	0.809